# THEKICKPLATESTORE
# SUGGESTED SPECIFICATIONS - SECTION 10 26 13
# MODEL MP-BAP-040834-SA
# 8" x 34" - BRASS KICK PLATE

## Part 1 - GENERAL

**1.01 SUMMARY**

**A.** This section includes the following types of wall protection systems:

**1.** Kickplates for door protection

**1.02 REFERENCES**

**A.** American Society for Testing and Materials (ASTM)

**1.03 SUBMITTALS**

**A.** General: Submit the following in accordance with conditions of contract and Division 1 specification section 01 33 00 "Submittal Procedures".

**B.** Product data and detailed specifications for each system component and installation accessory required, including installation methods for each type of substrate.

**C.** Shop drawings showing locations, extent and installation details of kickplates. Show methods of attachment to adjoining construction.

**D.** Samples for verification purposes: Submit the following samples, as proposed for this work, for verification of guard.

**E.** Product test reports from a qualified independent testing laboratory showing compliance of each component with requirements indicated.

**F.** Maintenance data for wall protection system components for inclusion in the operating and maintenance manuals specified in Division 1.

**1.04 DELIVERY, STORAGE AND HANDLING**

**A.** Deliver materials to the project site in unopened original factory packaging clearly labeled to show manufacturer.

**B.** Inspect materials at delivery to assure that specified products have been received.

**C.** Material must be stored flat in original packaging in a climate controlled location away from direct sunlight.

**D.** Handling: Take adequate measure to prevent damage to materials.

**1.05 PROJECT CONDITIONS**

**A.** Environmental Requirements: Products must be installed in an interior climate controlled environment.

**1.06 WARRANTY**

**A.** Standard TheKickPlateStore Limited Lifetime Warranty against material and manufacturing defects.

## Part 2 - PRODUCTS

**2.01 MANUFACTURER**

**A.** TheKickPlateStore
11445 E Via Linda, Suite 2 #323, Scottsdale, AZ 85259
2220 Fernbrook Lane North, Plymouth, MN 55447
Tel: 800-516-0436 Fax: 952-303-3773
sales@TheKickPlateStore.com

**B.** Substitutions: Not permitted

**C.** Provide all Brass Kickplates and wall protection from a single source.

**2.02 DESCRIPTION**

**A.** Model: **MP-BAP-040834-SA** | 8" (203.2mm) x 34" (863.6mm) Surface mounted brass kick plate. Use construction adhesive for standard installation. Available pre-drilled or pre-drilled and countersunk for use with mechanical fasteners. Custom sizes are available.

**2.03 MATERIALS**

**A.** Brass: Type Muntz, 0.04 gauge, with a #8 mirror finish.

**B.** Adhesive: Polyurethane based construction adhesive.

**2.04 FABRICATION**

**A.** Kick Plates shall be factory formed from brass sheet.

1. Edge burrs shall be removed.
2. Satin finish grain oriented parallel with length.
3. Optional beveled edge will have a 45° chamfer on 1 to 3 sides, dimension .030

**2.05 ACCESSORIES**

**A.** Mechanical Fasteners:

1. For Optional Pre-drilled Holes: Stainless steel #8 x 1 1/4" Philips oval head wood screw with stainless steel cup washer.
2. For Optional Pre-drilled and Countersunk Holes: Stainless steel #8 x 1 1/4" Philips oval head wood screw.
3. Tamper resistant fasteners available.

## Part 3 - EXECUTION

**3.01 EXAMINATION**

**A.** Verification of conditions: Examine areas and conditions under which work is to be performed and identify conditions detrimental to proper or timely completion.

1. Do not proceed until unsatisfactory conditions have been corrected.

**3.02 PREPARATION**

**A.** Surface preparation: Prior to installation, clean substrate to remove dirt, debris and loose particles. Perform additional preparation procedures as required by manufacturer's instructions.

**B.** Protection: Take all necessary steps to prevent damage to material during installation as required in manufacturer's installation instructions.

**3.03 INSTALLATION**

**A.** Install the work of this section in strict accordance with the manufacturer's recommendations, using only approved mounting hardware, and locating all components firmly into position, level and plumb.

**3.04 CLEANING**

**A.** General: Immediately upon completion of installation, clean material in accordance with manufacturer's recommended cleaning method.

**B.** Remove surplus materials, rubbish and debris resulting from installation as work progresses and upon completion of work.

**3.05 Protection**

**A.** Protect installed materials to prevent damage by other trades. Use materials that may be easily removed without leaving residue or permanent stains.